



Model #: S034-68I

SCSI/Fibre Channel - 68-in. Internal SCSI III Fast/Wide Ribbon Cable 8Conn HD68M



Highlights

Premium cabling

Description

This 68 inch SCSI III internal ribbon cable is used to connect up to 7 fast/wide SCSI devices to the SCSI host controller card. These devices require HD68M connectors and commonly include CD-ROM and hard drives. This cable has 8 high quality HD68M connectors: one for the SCSI host adapter and 7 for device connections. This cable is configured for use in most towers. The length of cable between the host controller and the first device is 20 inches and each device connector is spaced 8 inches apart. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

- Wide SCSI controller
- Wide SCSI drive or internal device

Package Includes

• 68-in. internal SCSI III fast/wide ribbon cable 8Conn HD68M

Features

- 68-in. long
- Supports transfer speeds up to 40Mbps
- Eight 68pin male (HD68M) fast/ wide SCSI connectors
- Internal 68in (5.8ft) 68pin wide SCSI ribbon cable with 8 connections used to connect internal devices requiring HD68M interface
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW	
Drives Supported	7
INPUT	

Cable Length (in.)	68	
CONNECTIONS		
Connector A	INTERNAL HD68 (MALE)	
Connector B	INTERNAL HD68 (MALE)	
Number of Connectors	8	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2348.

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.