APPLICA	BLE STAN	DARD									
OPERATING TEMPERATURE RAI		E RANGE	$=$ -35° C TO 85° C (NOTE 1) $_{\text{TE}}$		ТЕМ	PRAGE IPERATURE RANGE			-10°C TO 60°C		
RATING VOLTAGE			30V AC		1	APPLICABLE CONNECTOR		BM14B(0.8)-*DP-0.4		k*) V1	k)
CURRENT			0. 3A								
SPECIFICATIONS											
I	ГЕМ		TEST METHOD				RE	EQUI	REMENTS	QT	АТ
CONSTR	RUCTION	•									
GENERAL E	XAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				Х	Х
MARKING		CONFIRMED VISUALLY.								Х	Х
		CTERISTICS									
CONTACT RESISTANCE		20mV AC OR LESS 1kHz,1mA .				100mΩ MAX.				X	_
INSULATION RESISTANCE		100V DC.				50MΩ MIN.				Х	_
VOLTAGE PROOF		100V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				_	
MECHANICAL CHA		L ARACTERISTICS					X				
MECHANICAL		10TIMES INSERTIONS AND EXTRACTIONS.				① CONTACT RESISTANCE: 100mΩ MAX.					
OPERATION						② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				Х	_
VIBRATION		, , , , , , , , , , , , , , , , , , , ,				NO ELECTRICAL DISCONTINUITY OF 1 µs. NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	_
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				NO ELECTRICAL DISCONTINUITY OF 1 µs. NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				Х	_
ENVIRO	NMENTAL	CHAR	ACTERISTICS			1					
RAPID CHANGE OF		TEMPERATURE -55 → +85°C				① COI	NTACT RE	ESIS	TANCE: 100mΩ MAX.	.,	
TEMPERATURE		TIME 30 \rightarrow 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHANBER : WITHIN 2-3 min)				② INSULATION RESISTANCE: $50M\Omega$ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	_
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.				 CONTACT RESISTANCE: 100mΩ MAX. INSULATION RESISTANCE: 25MΩ MIN. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 				X	_
SULPHUR DIIOXIDE		EXPOSED IN 25 PPM FOR 96h,25°C,75%. (REFER TO JIS C 60068)				 CONTACT RESISTANCE: 100mΩ MAX. NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR. 				Х	_
COUN	IT DI	ESCRIPTION OF REVISIONS DESIG			NED			CHECKED	DA	TE	
Δ											
REMARKS NOTE1: INCLUDE THE TEMPERAT			TIRE RISING BY CLIPPENT				APPROV	ED	KH. IKEDA	11.0	2.02
INOTE I. INCL	ODE THE TEMP	LIVATORE	NATURE RISING DI CURRENI			CHECKED		_	AR. TAKAHASHI	11.02.02	
Unless otherwise specified, refe			r to JIS C 5402 and IEC 60512.			DESIGNED		\rightarrow	TR. YUNOK I TR. YUNOK I	11. 02. 02 11. 02. 02	
Note QT:Qualification Test AT:Ass						RAWING NO.			ELC4-322327-01		
שנו	91	PECIFI	PECIFICATION SHEET PA			RT NO.		W14	3 (0. 8) -*DS-0. 4V (5	52)	
HS.		OSE ELECTRIC CO., LTD.			CODE					▲ T	1/1