

Sleeve housing - VC-K-T3-R - 1855115

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Plastic sleeve housing, locking screws with knurled head, type 3, cable screw connection Pg21



Why buy this product

- Seals with two cable entries are available
- Management of the second secon



Key Commercial Data

Packing unit	5 STK
GTIN	4 017918 159276
GTIN	4017918159276

Technical data

Dimensions

Height	75 mm	
Ambient conditions		
Degree of protection	IP67	
Ambient temperature (operation)	-40 °C 80 °C	
General		
Note	When using fiber optics, the bending radii of the cable manufacturers must be observed.	
Туре	VC3	
Degree of protection	IP67	
Flammability rating according to UL 94	V0	
Locking type	Screw locking, knurled head	
Fixing screws	M4	
Tightening torque, mounting screw	1.5 Nm ±0.3 Nm	
Type of the screw connection	Pg21	



Sleeve housing - VC-K-T3-R - 1855115


Technical data

General


Cable outlet	Angled	
Housing material	Polyamide	
Seal material	EPDM	
Ambient temperature (operation)	-40 °C 80 °C	
Standards and Regulations		
Flammability rating according to UL 94	V0	
Environmental Product Compliance		
China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

Drawings


Dimensional drawing



Dimensional drawing



Dimensional drawing



Approvals

Approvals

Approvals

EAC

Ex Approvals



Sleeve housing - VC-K-T3-R - 1855115

EAC

Approvals

Approval details

EAC

B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com