



Part Number: 38314

UL Type PV Wire, (1) 14 AWG (41x30) TC, XLPE/PVC, 2000V, 90°C

Request Sample

Product Description

One 14 AWG stranded (41x30) tinned copper conductors, cross-linked polyethylene insulation, PVC jacket.

Technical Specifications

Product Overview

Suitable Applications: Interconnection wiring of grounded and ungrounded photovoltaic power systems as described in Section 690.31(A) of the 2008 NEC.

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
14	41x30	TC - Tinned Copper	1
Conductor Count: 1		1	
Condu	Conductor Size: 14 AWG		14 AWG

Insulation

Material	Nominal Wall Thickness
XLPE - Cross Linked Polyethylene	0.063 in
XLPE - Cross Linked Polyethylene	

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.273 in	0.033 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
2.4 Ohm/1000ft

Shielding: Unshielded

Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30 ambient	35.0 A

Voltage

Non-UL Voltage Rating	UL Description	UL Voltage Rating
600 V	PV, RHW-2	2000 V
	USE-2	600 V RMS

Temperature Range

UL Temp Rating:	90°C
Operating Temp Range:	-40°C To +90°C

Mechanical Characteristics

Bulk Cable Weight:	43 lbs/1000ft
Max Recommended Pulling Tension:	53.5 lbs

Min Bend Radius/Minor Axis:

Standards

UL AWM Style:	PV, USE-2, RHW-2
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2009-09-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Sunlight Resistance:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	2000 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No

Part Number

Variants

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.