

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	11MAY2015	DW	CW
	A1	ECR-17-018349	14DEC2017	DW	CW


NOTES:

1. TECHNICAL CHARACTERISTICS:
 CONTACT MATERIAL: BRASS
 SURFACE PLATING:
 SILVER PLATING: $\geq 2\mu\text{m}$
 CONTACT RESISTANCE: $\leq 0.5\text{m}\Omega$
 WIRE RANGE: 70 mm^2
 OPERATION TEMPERATURE: $-40\sim+125^\circ\text{C}$

注释:

1. 技术参数:
 公针材料: 黄铜
 表面电镀:
 镀银: $\geq 2\mu\text{m}$
 接触电阻: $\leq 0.5\text{m}\Omega$
 接线范围: 70 mm^2
 工作温度: $-40\sim+125^\circ\text{C}$

SECTION A-A

T2060002070-000	CHF-70	CHF-70, SILVER PLATING HMN-001母针 70mm^2 , 镀银	70	22.5
PART NUMBER 料号	PART DESCRIPTION 描述		WIRE GAUGE (mm^2) 线规 (mm^2)	STRIPPING LENGTH (mm) 剥线长度 (mm)
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 11MAY2015 David Wang	 TE Connectivity	
DIMENSIONS: mm		CHK 11MAY2015 Chris Wang		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 11MAY2015 Xiang Xu	NAME CHF-70 HM SOCKET CONTACT	
0 PLC \pm -		PRODUCT SPEC 108-137057	SIZE	
1 PLC \pm -		APPLICATION SPEC 114-137057	CAGE CODE	
2 PLC \pm -		WEIGHT	DRAWING NO	
3 PLC \pm -		Customer Drawing	A300779	
4 PLC \pm -			G-T2060002070000	
ANGLES \pm -			RESTRICTED TO	
FINISH			SCALE	
-			2:1	
-			SHEET	
			1 OF 1	
			REV	
			A1	

1470-19 (3/13)